National Semiconductor

LM1577/LM2577 Series SIMPLE SWITCHER[®] Step-Up Voltage Regulator

General Description

The LM1577/LM2577 are monolithic integrated circuits that provide all of the power and control functions for step-up (boost), flyback, and forward converter switching regulators. The device is available in three different output voltage versions: 12V, 15V, and adjustable.

Requiring a minimum number of external components, these regulators are cost effective, and simple to use. Listed in this data sheet are a family of standard inductors and flyback transformers designed to work with these switching regulators.

Included on the chip is a 3.0A NPN switch and its associated protection circuitry, consisting of current and thermal limiting, and undervoltage lockout. Other features include a 52 kHz fixed-frequency oscillator that requires no external components, a soft start mode to reduce in-rush current during start-up, and current mode control for improved rejection of input voltage and output load transients.

•

- Features
- Requires few external components
- NPN output switches 3.0A, can stand off 65V
 Wide input voltage range: 3.5V to 40V
- Write input voltage range. 3.57 to 407
 Current-mode operation for improved transient
- response, line regulation, and current limit
 52 kHz internal oscillator
- 52 KHz internal oscillator
- Soft-start function reduces in-rush current during start-up
 Output switch asstarted by surgert limit, and surgers
- Output switch protected by current limit, under-voltage lockout, and thermal shutdown

Typical Applications

- Simple boost regulator
- Flyback and forward regulators
- Multiple-output regulator



Note: Pin numbers shown are for TO-220 (T) package.

Ordering Information

Temperature	Package		Output Voltage		NSC	
Range	Туре	12V	15V	ADJ	Package	Package
					Drawing	
$-40^{\circ}C \le T_A \le +125^{\circ}C$	24-Pin Surface Mount	LM2577M-12	LM2577M-15	LM2577M-ADJ	M24B	SO
	16-Pin Molded DIP	LM2577N-12	LM2577N-15	LM2577N-ADJ	N16A	N
	5-Lead Surface Mount	LM2577S-12	LM2577S-15	LM2577S-ADJ	TS5B	TO-263
	5-Straight Leads	LM2577T-12	LM2577T-15	LM2577T-ADJ	T05A	TO-220
	5-Bent Staggered	LM2577T-12	LM2577T-15	LM2577T-ADJ	T05D	TO-220
	Leads	Flow LB03	Flow LB03	Flow LB03		
$-55^{\circ}C \le T_A \le +150^{\circ}C$	4-Pin TO-3	LM1577K-12/883	LM1577K-15/883	LM1577K-	K04A	TO-3
				ADJ/883		

SIMPLE SWITCHER® is a registered trademark of National Semiconductor Corporation

© 1999 National Semiconductor Corporation DS011468

June 1999

Absolute Maximum Ratings (Note 1)

· •

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/ Distributors for availability and specifications.

Supply Voltage	45V
Output Switch Voltage	65V
Output Switch Current (Note 2)	6.0A
Power Dissipation	Internally Limited
Storage Temperature Range	-65°C to +150°C
Lead Temperature	
(Soldering, 10 sec.)	260°C
Maximum Junction Temperature	150°C

Minimum ESD Rating

(C = 100 pF, R = 1.5 k Ω)

Operating Ratings

Supply Voltage	3.5
Output Switch Voltage	$0V \le V$
Output Switch Current	I,
Junction Temperature Range	
LM1577	–55°C :
LM2577	-40°C ≤

 $V \le V_{IN} \le 40V$ $V_{SWITCH} \le 60V$ $_{\rm SWITCH} \le 3.0 A$

2 kV

 $\leq T_{J} \leq +150^{\circ}C$ $\leq T_{J} \leq +125^{\circ}C$

Electrical Characteristics—LM1577-12, LM2577-12

Specifications with standard type face are for $T_J = 25^{\circ}C$, and those in **bold type face** apply over full **Operating Temperature Range**. Unless otherwise specified, $V_{IN} = 5V$, and $I_{SWITCH} = 0$.

Т

				LM1577-12	LM2577-12	Units
Symbol	Parameter	Conditions	Typical	Limit	Limit	(Limits)
				(Notes 3, 4)	(Note 5)	
SYSTEM PAR	AMETERS Circuit of Figu	ure 1 (Note 6)				
V _{OUT}	Output Voltage	$V_{IN} = 5V$ to 10V	12.0			V
		I_{LOAD} = 100 mA to 800 mA		11.60/ 11.40	11.60/ 11.40	V(min)
		(Note 3)		12.40/ 12.60	12.40/ 12.60	V(max)
ΔV _{OUT}	Line Regulation	V _{IN} = 3.5V to 10V 20				mV
ΔV_{IN}		I _{LOAD} = 300 mA		50/ 100	50/ 100	mV(max)
ΔV _{OUT}	Load Regulation	$V_{IN} = 5V$	20			mV
Δ_{LOAD}		I _{LOAD} = 100 mA to 800 mA		50/ 100	50/ 100	mV(max)
η	Efficiency	V _{IN} = 5V, I _{LOAD} = 800 mA	80			%
DEVICE PAR	AMETERS					
Is	Input Supply Current	V _{FEEDBACK} = 14V (Switch Off)	7.5			mA
				10.0/ 14.0	10.0/ 14.0	mA(max)
		I _{SWITCH} = 2.0A	25			mA
		V _{COMP} = 2.0V (Max Duty Cycle)		50/ 85	50/ 85	mA(max)
V _{UV}	Input Supply	I _{SWITCH} = 100 mA	2.90			V
	Undervoltage Lockout			2.70/ 2.65	2.70/ 2.65	V(min)
				3.10/ 3.15	3.10/ 3.15	V(max)
f _o	Oscillator Frequency	Measured at Switch Pin	52			kHz
		I _{SWITCH} = 100 mA		48/ 42	48/ 42	kHz(min)
				56/ 62	56/ 62	kHz(max)
V _{REF}	Output Reference	Measured at Feedback Pin				V
	Voltage	$V_{IN} = 3.5V$ to 40V	12	11.76/ 11.64	11.76/ 11.64	V(min)
		$V_{COMP} = 1.0V$		12.24/ 12.36	12.24/ 12.36	V(max)
ΔV_{REF}	Output Reference	$V_{IN} = 3.5V$ to 40V	7			mV
ΔV _{IN}	Voltage Line Regulator					
R _{FB}	Feedback Pin Input		9.7			kΩ
	Resistance					
G _M	Error Amp	$I_{COMP} = -30 \ \mu A$ to +30 μA	370			µmho
	Transconductance	$V_{COMP} = 1.0V$		225/ 145	225/ 145	µmho(min)
				515/ 615	515/ 615	µmho(max)
A _{VOL}	Error Amp	$V_{COMP} = 1.1V$ to 1.9V	80			V/V
	Voltage Gain	$R_{COMP} = 1.0 M\Omega$		50/ 25	50/ 25	V/V(min)
		(Note 7)				

Electric	al Characterist	ics—LM1577-12, LM2	577-12	Continued)		
Specifications Range. Unles	s with standard type face ss otherwise specified, V _I	are for $T_J = 25^{\circ}C$, and those in bold $_{N} = 5V$, and $I_{SWITCH} = 0$.	type face	apply over full (Operating Terr	perature
				LM1577-12	LM2577-12	Units
Symbol	Parameter	Conditions	Typical	Limit	Limit	(Limits)
				(Notes 3, 4)	(Note 5)	
DEVICE PAR	AMETERS		•			
	Error Amplifier	Upper Limit	2.4			V
	Output Swing	V _{FEEDBACK} = 10.0V		2.2/ 2.0	2.2/ 2.0	V(min)
		Lower Limit	0.3			V
		V _{FEEDBACK} = 15.0V		0.40/ 0.55	0.40/ 0.55	V(max)
	Error Amplifier	V _{FEEDBACK} = 10.0V to 15.0V	±200			μA
	Output Current	$V_{COMP} = 1.0V$		±130/ ±90	±130/ ±90	µA(min)
				±300/ ±400	±300/ ±400	µA(max)
I _{ss}	Soft Start Current	V _{FEEDBACK} = 10.0V	5.0			μA
		$V_{COMP} = 0V$		2.5/ 1.5	2.5/ 1.5	µA(min)
				7.5/ 9.5	7.5/ 9.5	µA(max)
D	Maximum Duty Cycle	$V_{COMP} = 1.5V$	95			%
		I _{SWITCH} = 100 mA		93/ 90	93/ 90	%(min)
ΔI _{SWITCH}	Switch		12.5			A/V
ΔV_{COMP}	Transconductance					
IL.	Switch Leakage	V _{SWITCH} = 65V	10			μA
	Current	V _{FEEDBACK} = 15V (Switch Off)		300/ 600	300/600	µA(max)
V _{SAT}	Switch Saturation	I _{SWITCH} = 2.0A	0.5			V
	Voltage	V _{COMP} = 2.0V (Max Duty Cycle)		0.7/ 0.9	0.7/0.9	V(max)
	NPN Switch		4.5			A
	Current Limit			3.7/ 3.0	3.7/ 3.0	A(min)
				5.3/ 6.0	5.3/ 6.0	A(max)

. .

Electrical Characteristics— LM1577-15, LM2577-15 Specifications with standard type face are for $T_J = 25$ °C, and those in **bold type face** apply over full **Operating Temperature** Range. Unless otherwise specified, $V_{IN} = 5V$, and $I_{SWITCH} = 0$.

				LM1577-15	LM2577-15	Units
Symbol	Parameter	Conditions	Typical	Limit	Limit	(Limits)
				(Notes 3, 4)	(Note 5)	
SYSTEM PARA	METERS Circuit of Figure .	2 (Note 6)				
V _{OUT}	Output Voltage	$V_{IN} = 5V$ to 12V	15.0			V
		I_{LOAD} = 100 mA to 600 mA		14.50/ 14.25	14.50/ 14.25	V(min)
		(Note 3)		15.50/ 15.75	15.50/ 15.75	V(max)
ΔV _{OUT}	Line Regulation	V _{IN} = 3.5V to 12V	20	50/400	50/100	mV
ΔVIN		I _{LOAD} = 300 mA		50/1 00	50/100	mV(max)
ΔV _{OUT}	Load Regulation	$V_{IN} = 5V$	20		50/ 100	mV
Δ_{LOAD}		I_{LOAD} = 100 mA to 600 mA		50/ 100		mV(max)
η	Efficiency	$V_{IN} = 5V, I_{LOAD} = 600 \text{ mA}$	80			%
DEVICE PARAM	METERS		•			
Is	Input Supply Current	V _{FEEDBACK} = 18.0V	7.5			mA
		(Switch Off)		10.0/ 14.0	10.0/ 14.0	mA(max)
		I _{SWITCH} = 2.0A	25			mA
		$V_{COMP} = 2.0V$		50/ 85	50/ 85	mA(max)
		(Max Duty Cycle)				
V _{UV}	Input Supply	I _{SWITCH} = 100 mA	2.90			V

Symbol	Parameter	Conditions	Typical	LM1577-15 Limit (Notes 3, 4)	LM2577-15 Limit (Note 5)	Units (Limits)
DEVICE PARA	METERS			× · · /	,	
	Undervoltage			2.70/ 2.65	2.70/ 2.65	V(min)
	Lockout			3.10/ 3.15	3.10/ 3.15	V(max)
f _o	Oscillator Frequency	Measured at Switch Pin	52			kHz
		I _{SWITCH} = 100 mA		48/ 42	48/ 42	kHz(min)
				56/ 62	56/ 62	kHz(max
V _{REF}	Output Reference	Measured at Feedback Pin				V
	Voltage	$V_{IN} = 3.5V \text{ to } 40V$	15	14.70/ 14.55	14.70/ 14.55	V(min)
		$V_{COMP} = 1.0V$		15.30/ 15.45	15.30/ 15.45	V(max)
ΔV_{REF}	Output Reference	$V_{IN} = 3.5V \text{ to } 40V$	10			mV
ΔV_{IN}	Voltage Line Regulation					
R _{FB}	Feedback Pin Input		12.2			kΩ
	Voltage Line Regulator					
G _M	Error Amp	$I_{COMP} = -30 \ \mu A$ to +30 μA	300			µmho
	Transconductance	$V_{COMP} = 1.0V$		170/ 110	170/ 110	µmho(min
				420/ 500	420/ 500	µmho(ma)
A _{VOL}	Error Amp	V_{COMP} = 1.1V to 1.9V	65			V/V
	Voltage Gain	$R_{COMP} = 1.0 M\Omega$		40/ 20	40/ 20	V/V(min)
		(Note 7)				
	Error Amplifier	Upper Limit	2.4			V
	Output Swing	V _{FEEDBACK} = 12.0V		2.2/ 2.0	2.2/ 2.0	V(min)
		Lower Limit	0.3			V
		V _{FEEDBACK} = 18.0V		0.4/ 0.55	0.40/ 0.55	V(max)
	Error Amp	$V_{\text{FEEDBACK}} = 12.0V \text{ to } 18.0V$	±200			μA
	Output Current	$V_{COMP} = 1.0V$		±130/ ±90	±130/ ±90	µA(min)
		10.01/		±300/ ±400	±300/ ±400	µA(max)
I _{SS}	Soft Start Current	V _{FEEDBACK} = 12.0V	5.0	0 5 / 	0.54.5	μΑ
		$V_{COMP} = 0V$		2.5/1.5	2.5/1.5	μA(min)
D	Maximum Duty		05	7.5/9.5	7.5/9.5	µA(max)
D		$V_{\rm COMP} = 1.5V$	95	02/00	02/00	% 0/(min)
	Cycle	I _{SWITCH} = 100 mA	12.5	93/90	93/90	%(mm)
ΔI_{SWITCH} ΔV_{COMP}	Transconductance		12.5			A/V
I	Switch Leakage	V _{SWITCH} = 65V	10			μA
	Current	V _{FEEDBACK} = 18.0V (Switch Off)		300/ 600	300/ 600	µA(max)
V _{SAT}	Switch Saturation	I _{SWITCH} = 2.0A	0.5			V
	Voltage	$V_{COMP} = 2.0V$		0.7/ 0.9	0.7/ 0.9	V(max)
		(Max Duty Cycle)				
	NPN Switch	$V_{COMP} = 2.0V$	4.3			A
	Current Limit			3.7/ 3.0	3.7/ 3.0	A(min)
				5.3/ 6.0	5.3/ 6.0	A(max)

· ·

0	P		-	LM1577-ADJ	LM2577-ADJ	Units
Symbol	Parameter	Conditions	Iypical	Limit	Limit	(Limits)
SVSTEM D	ADAMETERS Circuit of <i>Ei</i>	auro 2 (Noto 6)		(Notes 3, 4)	(Note 5)	
/	ARAMETERS Circuit of Fi		12.0			M
OUT	Oulput voltage	$V_{\rm IN} = 500 {\rm m}$ to 800 m Å	12.0	11 60/11 40	11 60/11 10	V \/(min)
		(Note 2)		12.40/12.60	12.40/12.60	V(IIIII)
N/ /	Line Regulation	(NOTE 3)	20	12.40/12.00	12.40/12.00	v(mldx)
VOUT		$v_{\rm IN} = 3.5 v \ 10 \ 10 v$	20	50/100	E0/ 100	m\/(mov)
1V _{IN}	Load Pogulation	$I_{LOAD} = 500 \text{ IIIA}$	20	50/100	50/100	m\/
V OUT		$v_{\rm IN} = 3v$	20	50/100	50/100	m\/(max)
	Efficionov	$V_{LOAD} = 100 \text{ mA} \text{ to 800 mA}$	00	30/100	30/100	0/.
		V _{IN} = 5V, I _{LOAD} = 800 IIIA	00			/0
		$1 = 1.5 \sqrt{(Switch Off)}$	7.5	1	1	m۸
S		VFEEDBACK - 1.5V (Switch Off)	7.5	10.0/14.0	10.0/14.0	mA(max)
		2.04	25	10.0/14.0	10.0/14.0	mA
		$I_{SWITCH} = 2.0A$	25	50/95	50/ 85	mA(max)
/	Input Supply	$V_{COMP} = 2.00$ (Wax Duty Cycle)	2.00	30/83	30/83	
/ UV	Input Suppry	ISWITCH - 100 IIIA	2.90	2 70/2 65	2 70/2 65	V \/(min)
	Ondervoltage Lockout			2.10/2.05	2.10/2.05	
		Measured at Switch Pin	52	3.10/3.13	3.10/3.13	kHz
0	Oscillator Trequency	I = 100 mA	52	18/12	48/ 42	kHz(min)
		ISWITCH - 100 IIIA		56/ 62	56/ 62	kHz(may
/	Reference	Measured at Feedback Pin		00/02	00/02	V
REF	Voltage	V = 3.5 V to 40 V	1 230	1 21//1 206	1 21//1 206	V(min)
	Vollage	$V_{\rm IN} = 3.50 \text{ to 400}$	1.200	1 246/1 254	1.214/1.200	V(max)
····	Reference Voltage	$V_{\rm COMP} = 3.5 V$ to $40 V$	0.5	1.240/1.204	1.240/1.204	m\/
VREF	Line Regulation	V _{IN} = 3.3V 10 40V	0.5			IIIV
	Error Amp	$V_{acus} = 1.0V$	100			nA
В	Input Bias Current	COMP 1.0V	100	300/800	300/ 800	nA(max)
3	Frror Amp	$l_{\text{acup}} = -30 \text{ uA to } +30 \text{ uA}$	3700	000,000	000/000	umho
M	Transconductance	$V_{\text{COMP}} = 1.0V$	0100	2400/ 1600	2400/ 1600	umho(mir
	Trancoonadotanoo	COMP 1.0V		4800/5800	4800/ 5800	umho(ma
Avoi	Error Amp	$V_{COMP} = 1.1V \text{ to } 1.9V$	800		1000,0000	V/V
VOL	Voltage Gain	$B_{\text{COMP}} = 1.0 \text{ MO} \text{ (Note 7)}$		500/250	500/ 250	V/V(min)
	Fror Amplifier		24	000,200	000/200	V
	Output Swing	$V_{\text{FFFDDAOK}} = 1.0V$		2 2/2.0	2 2/2.0	V(min)
		Lower Limit	0.3			V
		$V_{FFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFF$		0 40/0.55	0 40/0.55	V(max)
	Error Amp	$V_{\text{FEEDBACK}} = 1.0V \text{ to } 1.5V$	±200			цА
	Output Current	$V_{COMP} = 1.0V$	-200	±130/ ±90	±130/ ±90	uA(min)
				±300/±400	±300/±400	
~~	Soft Start Current	VEEEDBACK = 1.0V	5.0			uА
66		$V_{COMP} = 0V$	5.0	2.5/1.5	2.5/1.5	μA(min)
				7.5/9.5	7.5/9.5	uA(max)
)	Maximum Duty Cycle	$V_{COMP} = 1.5V$	95			%
-				93/90	93/ 90	%(min)
Newara /	Switch	SWITCH SOUND	12.5			A/V
SWIICH						

Symbol	Parameter	Conditions	Typical	LM1577-ADJ Limit (Notes 3 4)	LM2577-ADJ Limit (Note 5)	Units (Limits
DEVICE PA	RAMETERS			((
1	Switch Leakage	V _{SWITCH} = 65V	10			μA
	Current	$V_{\text{FFFDBACK}} = 1.5V$ (Switch Off)		300/ 600	300/ 600	µA(max
/ _{SAT}	Switch Saturation	I _{SWITCH} = 2.0A	0.5			V
	Voltage	V _{COMP} = 2.0V (Max Duty Cycle)		0.7/ 0.9	0.7/ 0.9	V(max)
	NPN Switch	V _{COMP} = 2.0V	4.3			А
	Current Limit			3.7/ 3.0	3.7/ 3.0	A(min)
				5.3/ 6.0	5.3/ 6.0	A(max)
FHERMAL I	PARAMETERS (All Vers	ions)				
) _{JA}	Thermal Resistance	K Package, Junction to Ambient	35			
) _{JC}		K Package, Junction to Case	1.5			
JA		T Package, Junction to Ambient	65			
JC		T Package, Junction to Case	2			
) _{JA}		N Package, Junction to	85			°C/W
	_	Ambient (Note 8)				0,11
) _{JA}		M Package, Junction	100			
		to Ambient (Note 8)				
) _{JA}		S Package, Junction to	37			
		Ambient (Note 9)				
Note 3: All li	mite quaranteed at room temper	ontor regulator in accordance to the reprication				
Level, and ar Note 4: A mi RETS specifi to Standard I Note 5: All li tion tested. A Note 6: Exte as shown in I Note 7: A 1.0 this pin's loar Note 8: Juno resistance fu	Inits guaranteed at room temperature er 100% production tested. ilitary RETS electrical test specifications complied fully with the bo Wilitary Drawing specifications. mits guaranteed at room temper all limits at temperature extremes ernal components such as the dio the Test Circuit, system perform 0 MΩ resistor is connected to the d resistance should be $\geq 10 M\Omega$, ction to ambient thermal resistant rther. See thermal model in "Sw	ture (standard type face) and at temperature ext cation is available on request. At the time of prin Idface limits in these columns. The LM1577K-12 ature (standard type face) and at temperature ex- are guaranteed via correlation using standard de, inductor, input and output capacitors can affe ance will be as specified by the system paramel o compensation pin (which is the error amplifier's resulting in A _{VOL} that is typically twice the guar ex with approximately 1 square inch of pc board of theres. Made Simple" software.	remes (boldfac hting, the LM15 /883, LM1577k ktremes (boldfa Statistical Qual ct switching reg lers. output) to ens anteed minimu copper surroun	e type). All limits are 77K-12/883, LM157 (-15/883, and LM157 ice type). All room te ity Control (SQC) m julator performance. ure accuracy in mea m limit. ding the leads. Addit	used to calculate Ou 7K-15/883, and LM1 7K-ADJ/883 may als mperature limits are ethods. When the LM1577/LI suring A _{VOL} . In actua ional copper area will	itgoir 577K so be 1009 M257 Al app lowe

· ·





8









STEP-UP (BOOST) REGULATOR

Figure 4 shows the LM1577-ADJ/LM2577-ADJ used as a Step-Up Regulator. This is a switching regulator used for producing an output voltage greater than the input supply voltage. The LM1577-12/LM2577-12 and LM1577-15/LM2577-15 can also be used for step-up regulators with 12V or 15V outputs (respectively), by tying the feedback pin directly to the regulator output.

A basic explanation of how it works is as follows. The LM1577/LM2577 turns its output switch on and off at a frequency of 52 kHz, and this creates energy in the inductor (L). When the NPN switch turns on, the inductor current charges up at a rate of V_{IN}/L, storing current in the inductor. When the switch turns off, the lower end of the inductor flies above VIN, discharging its current through diode (D) into the output capacitor (C_{OUT}) at a rate of (V_{OUT} - V_{IN})/L. Thus, energy stored in the inductor during the switch on time is transferred to the output during the switch off time. The output voltage is controlled by the amount of energy transferred which, in turn, is controlled by modulating the peak inductor current. This is done by feeding back a portion of the output voltage to the error amp, which amplifies the difference between the feedback voltage and a 1.230V reference. The error amp output voltage is compared to a voltage proportional to the switch current (i.e., inductor current during the switch on time).

The comparator terminates the switch on time when the two voltages are equal, thereby controlling the peak switch current to maintain a constant output voltage.

Voltage and current waveforms for this circuit are shown in *Figure 5*, and formulas for calculating them are given in *Figure 6*.



Duty Cycle	D	$\frac{V_{OUT}+V_{F}-V_{IN}}{V_{OUT}+V_{F}-V_{SAT}}\approx\frac{V_{OUT}-V_{IN}}{V_{OUT}}$
Average Inductor Current	I _{IND(AVE)}	<u>lload</u> 1 − D
Inductor Current Ripple	ΔI_{IND}	$\frac{V_{IN} - V_{SAT}}{L} \frac{D}{52,000}$
Peak Inductor Current	I _{IND(PK)}	$\frac{I_{LOAD(max)}}{1 - D_{(max)}} + \frac{\Delta I_{IND}}{2}$
Peak Switch Current	I _{SW(PK)}	$\frac{I_{LOAD(max)}}{1 - D_{(max)}} + \frac{\Delta I_{IND}}{2}$
Switch Voltage When Off	V _{SW(OFF)}	V _{OUT} + V _F
Diode Reverse Voltage	V _R	V _{OUT} – V _{SAT}
Average Diode Current	I _{D(AVE)}	I _{LOAD}
Peak Diode Current	I _{D(PK)}	$\frac{I_{LOAD}}{1-D_{(max)}} + \frac{\Delta I_{IND}}{2}$
Power Dissipation of I M1577/2577	P _D	$0.25\Omega \left(\frac{I_{LOAD}}{1-D}\right)^2 D + \frac{I_{LOAD} D V_{IN}}{50 (1-D)}$

V_F = Forward Biased Diode Voltage

ILOAD = Output Load Current

FIGURE 6. Step-Up Regulator Formulas

STEP-UP REGULATOR DESIGN PROCEDURE

The following design procedure can be used to select the appropriate external components for the circuit in *Figure 4*, based on these system requirements.

Given:

 $V_{IN (min)}$ = Minimum input supply voltage

V_{OUT} = Regulated output voltage

I_{LOAD(max)} = Maximum output load current

Before proceeding any further, determine if the LM1577/ LM2577 can provide these values of V_{OUT} and I_{LOAD(max)} when operating with the minimum value of V_{IN}. The upper limits for V_{OUT} and I_{LOAD(max)} are given by the following equations.

 $V_{OUT} \le 60V$

and
$$V_{OUT} \leq 10 \times V_{IN(min)}$$

$$I_{LOAD(max)} \le \frac{2.1A \times V_{IN(min)}}{V_{OUT}}$$

These limits must be greater than or equal to the values specified in this application.

- 1. Inductor Selection (L)
 - A. Voltage Options:
 - 1. For 12V or 15V output

From Figure 7 (for 12V output) or Figure 8 (for 15V output), identify inductor code for region indicated by $V_{\rm IN~(min)}$ and I_{LOAD (max)}. The shaded region indicates conditions for which the LM1577/LM2577 output switch would be operating beyond its switch current rating. The minimum operating voltage for the LM1577/LM2577 is 3.5V.

From here, proceed to step C.

2. For Adjustable version

Preliminary calculations:

The inductor selection is based on the calculation of the following three parameters:

 $D_{(max)},$ the maximum switch duty cycle (0 \leq D \leq 0.9):

$$D_{(max)} = \frac{V_{OUT} + V_F - V_{IN(min)}}{V_{OUT} + V_F - 0.6V}$$

where V_{F} = 0.5V for Schottky diodes and 0.8V for fast recovery diodes (typically);

 $E \bullet T$, the product of volts x time that charges the inductor:

$$\mathsf{E} \bullet \mathsf{T} = \frac{\mathsf{D}_{(\text{max})} \, (\mathsf{V}_{\text{IN}(\text{min})} - 0.6\mathsf{V}) 10^6}{52,000 \, \text{Hz}} \qquad (\mathsf{V} \bullet \mu s)$$

I_{IND.DC}, the average inductor current under full load;

$$I_{\text{IND,DC}} = \frac{1.05 \times I_{\text{LOAD(max)}}}{1 - D_{\text{(max)}}}$$

B. Identify Inductor Value:

1. From *Figure 9*, identify the inductor code for the region indicated by the intersection of E•T and I_{IND,DC}. This code gives the inductor value in microhenries. The L or H prefix signifies whether the inductor is rated for a maximum E•T of 90 V•µs (L) or 250 V•µs (H).

2. If D < 0.85, go on to step C. If D \geq 0.85, then calculate the minimum inductance needed to ensure the switching regulator's stability:

$$L_{MIN} = \frac{6.4 (V_{IN(min)} - 0.6V) (2D_{(max)} - 1)}{1 - D_{(max)}} \quad (\mu H)$$

If $L_{\rm MIN}$ is smaller than the inductor value found in step B1, go on to step C. Otherwise, the inductor value found in step B1 is too low; an appropriate inductor code should be obtained from the graph as follows:

1. Find the lowest value inductor that is greater than L_{MIN} . 2. Find where E•T intersects this inductor value to determine if it has an L or H prefix. If E•T intersects both the L and H regions, select the inductor with an H prefix.







FIGURE 8. LM2577-15 Inductor Selection Guide



Inductor	Manufa	cturer's Part Nu	ımber
Code	Schott	Pulse	Renco
L47	67126980	PE - 53112	RL2442
L68	67126990	PE - 92114	RL2443
L100	67127000	PE - 92108	RL2444
L150	67127010	PE - 53113	RL1954
L220	67127020	PE - 52626	RL1953
L330	67127030	PE - 52627	RL1952
L470	67127040	PE - 53114	RL1951
L680	67127050	PE - 52629	RL1950
H150	67127060	PE - 53115	RL2445
H220	67127070	PE - 53116	RL2446
H330	67127080	PE - 53117	RL2447
H470	67127090	PE - 53118	RL1961
H680	67127100	PE - 53119	RL1960
H1000	67127110	PE - 53120	RL1959
H1500	67127120	PE - 53121	RL1958
H2200	67127130	PE - 53122	RL2448

Schott Corp., (612) 475-1173

1000 Parkers Lake Rd., Wayzata, MN 55391 Pulse Engineering, (619) 268-2400 P.O. Box 12235, San Diego, CA 92112

Renco Electronics Inc., (516) 586-5566 60 Jeffryn Blvd. East, Deer Park, NY 11729

FIGURE 10. Table of Standardized Inductors and Manufacturer's Part Numbers

2. Compensation Network (R_c, C_c) and Output Capacitor (C_{OUT}) Selection

R_C and C_C form a pole-zero compensation network that stabilizes the regulator. The values of R_C and C_C are mainly dependant on the regulator voltage gain, $I_{\text{LOAD}(\text{max})},\ L$ and C_{OUT}. The following procedure calculates values for R_C, C_C, and $C_{\mbox{\scriptsize OUT}}$ that ensure regulator stability. Be aware that this procedure doesn't necessarily result in R_c and C_c that provide optimum compensation. In order to guarantee optimum compensation, one of the standard procedures for testing loop stability must be used, such as measuring $V_{\mbox{\scriptsize OUT}}$ transient response when pulsing ILOAD (see Figure 15).

A. First, calculate the maximum value for R_C.

$$R_C \leq \frac{750 \times I_{LOAD(max)} \times V_{OUT}^2}{V_{IN(min)}^2}$$

Select a resistor less than or equal to this value, and it should also be no greater than 3 k $\!\Omega.$

B. Calculate the minimum value for COUT using the following two equations.

$$C_{\text{OUT}} \geq \frac{0.19 \times L \times \text{R}_{C} \times \text{I}_{\text{LOAD(max)}}}{\text{V}_{\text{IN(min)}} \times \text{V}_{\text{OUT}}}$$

and

$$C_{OUT} \geq \frac{V_{IN(min)} \times R_C \times (V_{IN(min)} + (3.74 \times 10^5 \times L))}{487,800 \times V_{OUT}^3}$$

The larger of these two values is the minimum value that ensures stability.

C. Calculate the minimum value of C_C .

www.national.com

$$C_{C} \geq \frac{58.5 \times V_{OUT}^{2} \times C_{OUT}}{R_{C}^{2} \times V_{IN(min)}}$$

The compensation capacitor is also part of the soft start circuitry. When power to the regulator is turned on, the switch duty cycle is allowed to rise at a rate controlled by this capacitor (with no control on the duty cycle, it would immediately rise to 90%, drawing huge currents from the input power supply). In order to operate properly, the soft start circuit requires $C_C \geq 0.22~\mu\text{F}.$

The value of the output filter capacitor is normally large enough to require the use of aluminum electrolytic capacitors. Figure 11 lists several different types that are recommended for switching regulators, and the following parameters are used to select the proper capacitor.

Working Voltage (WVDC): Choose a capacitor with a working voltage at least 20% higher than the regulator output voltage

Ripple Current: This is the maximum RMS value of current that charges the capacitor during each switching cycle. For step-up and flyback regulators, the formula for ripple current is

$$I_{\text{RIPPLE}(\text{RMS})} = \frac{I_{\text{LOAD}(\text{max})} \times D_{(\text{max})}}{1 - D_{(\text{max})}}$$

Choose a capacitor that is rated at least 50% higher than this value at 52 kHz.

Equivalent Series Resistance (ESR) : This is the primary cause of output ripple voltage, and it also affects the values of R_C and C_C needed to stabilize the regulator. As a result, the preceding calculations for C_C and R_C are only valid if ESR doesn't exceed the maximum value specified by the following equations.

$$\text{ESR} \leq \frac{0.01 \times \text{V}_{\text{OUT}}}{\text{I}_{\text{RIPPI F}(P,P)}} \text{ and } \leq \frac{8.7 \times (10) - 3 \times \text{V}_{\text{IN}}}{\text{I}_{\text{I}} \text{ OAD(max)}}$$

where

$$I_{\text{RIPPLE}(\text{P-P})} = \frac{1.15 \times I_{\text{LOAD(max)}}}{1 - D_{(\text{max})}}$$

Select a capacitor with ESR, at 52 kHz, that is less than or equal to the lower value calculated. Most electrolytic capacitors specify ESR at 120 Hz which is 15% to 30% higher than at 52 kHz. Also, be aware that ESR increases by a factor of 2 when operating at -20°C.

In general, low values of ESR are achieved by using large value capacitors (C \geq 470 $\mu\text{F}),$ and capacitors with high WVDC, or by paralleling smaller-value capacitors.

3. Output Voltage Selection (R1 and R2)

This section is for applications using the LM1577-ADJ/ LM2577-ADJ. Skip this section if the LM1577-12/LM2577-12 or LM1577-15/LM2577-15 is being used.

With the LM1577-ADJ/LM2577-ADJ, the output voltage is given by

$$V_{OUT} = 1.23V (1 + R1/R2)$$

Resistors R1 and R2 divide the output down so it can be compared with the LM1577-ADJ/LM2577-ADJ internal 1.23V reference. For a given desired output voltage V_{OUT} , select R1 and R2 so that

$$\frac{\text{R1}}{\text{R2}} = \frac{\text{V}_{\text{OUT}}}{1.23\text{V}} - 1$$

4. Input Capacitor Selection (CIN)

The switching action in the step-up regulator causes a triangular ripple current to be drawn from the supply source. This in turn causes noise to appear on the supply voltage. For proper operation of the LM1577, the input voltage should be decoupled. Bypassing the Input Voltage pin directly to ground with a good quality, low ESR, 0.1 μ F capacitor (leads as short as possible) is normally sufficient.

Cornell Dublier — Types 239, 250, 251, UFT,
300, or 350
P.O. Box 128, Pickens, SC 29671 (803) 878-6311
Nichicon — Types PF, PX, or PZ
927 East Parkway,
Schaumburg, IL 60173
(708) 843-7500

Sprague — Types 672D, 673D, or 674D Box 1, Sprague Road,

Lansing, NC 28643 (919) 384-2551

United Chemi-Con — Types LX, SXF, or SXJ 9801 West Higgins Road, Rosemont, IL 60018 (708) 696-2000

FIGURE 11. Aluminum Electrolytic Capacitors Recommended for Switching Regulators

If the LM1577 is located far from the supply source filter capacitors, an additional large electrolytic capacitor (e.g. 47 $\mu F)$ is often required.

5. Diode Selection (D)

The switching diode used in the boost regulator must withstand a reverse voltage equal to the circuit output voltage, and must conduct the peak output current of the LM2577. A suitable diode must have a minimum reverse breakdown voltage greater than the circuit output voltage, and should be rated for average and peak current greater than $I_{LOAD(max)}$ and $I_{D(PK)}$. Schottky barrier diodes are often favored for use in switching regulators. Their low forward voltage drop allows higher regulator efficiency than if a (less expensive) fast recovery diode was used. See *Figure 12* for recommended part numbers and voltage ratings of 1A and 3A diodes.

V _{OUT}	Schottky		Fast Recovery	
(max)	1A	3A	1A	3A
20V	1N5817	1N5820		
	MBR120P	MBR320P		
	1N5818	1N5821		
30V	MBR130P	MBR330P		
	11DQ03	31DQ03		
	1N5819	1N5822		
40V	MBR140P	MBR340P		
	11DQ04	31DQ04		
	MBR150	MBR350	1N4933	
50V	11DQ05	31DQ05	MUR105	
			1N4934	MR851
100V			HER102	30DL1
			MUR110	MR831
			10DL1	HER302

FIGURE 12. Diode Selection Chart

BOOST REGULATOR CIRCUIT EXAMPLE

By adding a few external components (as shown in *Figure 13*), the LM2577 can be used to produce a regulated output voltage that is greater than the applied input voltage. Typical performance of this regulator is shown in *Figure 14* and *Figure 15*. The switching waveforms observed during the operation of this circuit are shown in *Figure 16*.

www.national.com

FLYBACK REGULATOR

A Flyback regulator can produce single or multiple output voltages that are lower or greater than the input supply voltage. Figure 18 shows the LM1577/LM2577 used as a flyback regulator with positive and negative regulated outputs. Its operation is similar to a step-up regulator, except the output switch contols the primary current of a flyback transformer. Note that the primary and secondary windings are out of phase, so no current flows through secondary when current flows through the primary. This allows the primary to charge up the transformer core when the switch is on. When the switch turns off, the core discharges by sending current through the secondary, and this produces voltage at the outputs. The output voltages are controlled by adjusting the peak primary current, as described in the step-up regulator section

Voltage and current waveforms for this circuit are shown in Figure 17, and formulas for calculating them are given in Figure 19.

FLYBACK REGULATOR DESIGN PROCEDURE

1. Transformer Selection

D1, D2 = 1N5821

A family of standardized flyback transformers is available for creating flyback regulators that produce dual output voltages, from ±10V to ±15V, as shown in Figure 18. Figure 20lists these transformers with the input voltage, output voltages and maximum load current they are designed for.

2. Compensation Network (C_c, R_c) and Output Capacitor (COUT) Selection

As explained in the Step-Up Regulator Design Procedure, C_C, R_C and C_{OUT} must be selected as a group. The following procedure is for a dual output flyback regulator with equal turns ratios for each secondary (i.e., both output voltages have the same magnitude). The equations can be used for a single output regulator by changing $\Sigma I_{\text{LOAD}(\text{max})}$ to $I_{\text{LOAD}(\text{max})}$ in the following equations.

$$R_C \leq \frac{750 \times \Sigma I_{LOAD(max)} \times (15V + V_{IN(min)}N)^2}{V_{IN(min)}^2}$$

Where $\Sigma I_{\text{LOAD}(\text{max})}$ is the sum of the load current (magnitude) required from both outputs. Select a resistor less than or equal to this value, and no greater than 3 k Ω .

B. Calculate the minimum value for $\Sigma \textbf{C}_{\textbf{OUT}}$ (sum of $\textbf{C}_{\textbf{OUT}}$ at both outputs) using the following two equations.

$$C_{OUT} \geq \frac{0.19 \times R_{C} \times L_{P} \times \Sigma I_{LOAD(max)}}{15V \times V_{IN(min)}}$$

and

$$C_{OUT} {\geq} \frac{V_{IN(min)} {\times} R_C {\times} N^2 {\times} (V_{IN(min)} + (3.74 {\times} 10^5 {\times} L_p))}{487,800 {\times} (15V)^2 {\times} (15V {+} V_{IN(min)} {\times} N)}$$

The larger of these two values must be used to ensure regulator stability.

FIGURE 17. Flyback Regulator Waveforms

FIGURE 18. LM1577-ADJ/LM2577-ADJ Flyback Regulator with ± Outputs

19

.

Duty Cycle	D	
Duty Cycle		$\sim \frac{v_{OUT} + v_F}{2} \approx$
		$N (V_{IN} - V_{SAT}) + V_{OUT} + V_{F}$
		V _{OUT}
		$N (V_{IN}) + V_{OUT}$
Primary Current Variation		$D(V_{IN} - V_{SAT})$
	Δl _P	L _P × 52,000
Peak Primary Current		Ν., ΣΙ _{LOAD} , ΔΙΡΚ
	I _{P(PK)}	$\frac{1}{\eta} \times \frac{1}{1-D} + \frac{1}{2}$
Switch Voltage when Off		Vout + VF
	V _{SW(OFF)}	$V_{IN} + \frac{V_{IN}}{N}$
Diode Reverse Voltage	V _R	$V_{OUT}^+ N (V_{IN}^- V_{SAT})$
Average Diode Current	I _{D(AVE)}	I _{LOAD}
Peak Diode Current		I _{LOAD} ΔI _{IND}
	I _{D(PK)}	$\frac{1-D}{1-2}$
Short Circuit Diode Current		6A
		≈ <u>N</u>
Power Dissipation of		$(N \Sigma I_{IOAD})^2$
LM1577/LM2577		$\int 0.25\Omega \left(\frac{1-D}{1-D} \right)^{-+}$
	PD	N ILOADD
		$\frac{1}{50(1-D)}$ V _{IN}

N = Transformer Turns Ratio = number of secondary turns

 η = Transformer Efficiency (typically 0.95)

 $\Sigma I_{\text{LOAD}} = |+I_{\text{LOAD}}|+|-I_{\text{LOAD}}|$

FIGURE 19. Flyback Regulator Formulas

C. Calculate the minimum value of C_C

$$C_{C} \geq \frac{58.5 \times C_{OUT} \times V_{OUT} \times (V_{OUT} + (V_{IN(min)} \times N))}{R_{C}^{2} \times V_{IN(min)} \times N}$$

D. Calculate the maximum ESR of the +V_{OUT} and -V_{OUT} output capacitors in parallel.

$$\mathsf{ESR} + \|\mathsf{ESR}_{-} \leq \frac{8.7 \times 10^{-3} \times \mathsf{V}_{\mathsf{IN}(\mathsf{min})} \times \mathsf{V}_{\mathsf{OUT}} \times \mathsf{N}}{\Sigma \mathsf{I}_{\mathsf{LOAD}(\mathsf{max})} \times (\mathsf{V}_{\mathsf{OUT}}^{+} (\mathsf{V}_{\mathsf{IN}(\mathsf{min})} \times \mathsf{N}))}$$

This formula can also be used to calculate the maximum ESR of a single output regulator.

At this point, refer to this same section in the **Step-Up Regulator Design Procedure** for more information regarding the selection of C_{OUT} .

3. Output Voltage Selection

This section is for applications using the LM1577-ADJ/ LM2577-ADJ. Skip this section if the LM1577-12/LM2577-12 or LM1577-15/LM2577-15 is being used.

With the LM1577-ADJ/LM2577-ADJ, the output voltage is given by

Resistors R1 and R2 divide the output voltage down so it can be compared with the LM1577-ADJ/LM2577-ADJ internal 1.23V reference. For a desired output voltage V_{OUT} , select R1 and R2 so that

$$\frac{\mathrm{R1}}{\mathrm{R2}} = \frac{\mathrm{V}_{\mathrm{OUT}}}{\mathrm{1.23V}} - 1$$

4. Diode Selection

DS011468-78

The switching diode in a flyback converter must withstand the reverse voltage specified by the following equation.

$$v_{\mathsf{R}} = v_{\mathsf{OUT}} + \frac{v_{\mathsf{IN}}}{\mathsf{N}}$$

A suitable diode must have a reverse voltage rating greater than this. In addition it must be rated for more than the average and peak diode currents listed in *Figure 19*.

5. Input Capacitor Selection

The primary of a flyback transformer draws discontinuous pulses of current from the input supply. As a result, a flyback regulator generates more noise at the input supply than a step-up regulator, and this requires a larger bypass capacitor to decouple the LM1577/LM2577 $V_{\rm IN}$ pin from this noise. For most applications, a low ESR, $1.0~\mu{\rm F}$ cap will be sufficient, if it is connected very close to the $V_{\rm IN}$ and Ground pins.

Application Hints (Continued)						
Transformer		Input	Dual	Maxi- mum		
	Туре	Voltage	Output	Output		
			Voltage	Current		
	L _P = 100 µH	5V	±10V	325 mA		
1	N = 1	5V	±12V	275 mA		
		5V	±15V	225 mA		
		10V	±10V	700 mA		
		10V	±12V	575 mA		
2	L _P = 200 μH	10V	±15V	500 mA		
	N = 0.5	12V	±10V	800 mA		
		12V	±12V	700 mA		
		12V	±15V	575 mA		
3	L _P = 250 μH	15V	±10V	900 mA		
	N = 0.5	15V	±12V	825 mA		
		15V	±15V	700 mA		

Transformer	Manufacturers' Part Numbers			
Туре	AIE	Pulse	Renco	
1	326-0637	PE-65300	RL-2580	
2	330-0202	PE-65301	RL-2581	
3	330-0203	PE-65302	RL-2582	

FIGURE 20. Flyback Transformer Selection Guide

In addition to this bypass cap, a larger capacitor (\geq 47 $\mu\text{F})$ should be used where the flyback transformer connects to the input supply. This will attenuate noise which may interfere with other circuits connected to the same input supply voltage.

6. Snubber Circuit

A "snubber" circuit is required when operating from input voltages greater than 10V, or when using a transformer with $L_P \ge 200 \ \mu$ H. This circuit clamps a voltage spike from the transformer primary that occurs immediately after the output switch turns off. Without it, the switch voltage may exceed the 65V maximum rating. As shown in *Figure 21*, the snubber consists of a fast recovery diode, and a parallel RC. The

RC values are selected for switch clamp voltage (V_{CLAMP}) that is 5V to 10V greater than V_{SW(OFF)}. Use the following equations to calculate R and C;

$$\begin{split} C &\geq \frac{0.02 \times L_P \times I_{P(PK)}^2}{\left(V_{CLAMP}\right)^2 - \left(VSW_{(OFF)}\right)^2} \\ R &\leq \left(\frac{V_{CLAMP} + V_{SW(OFF)} - V_{IN}}{2}\right)^2 \times \left(\frac{19.2 \times 10^{-4}}{L_P \times I_{P(PK)}^2}\right) \end{split}$$

Power dissipation (and power rating) of the resistor is;

$$\mathsf{P} = \left(\frac{\mathsf{V}_{\mathsf{CLAMP}} + \mathsf{V}_{\mathsf{SW}(\mathsf{OFF})} - \mathsf{V}_{\mathsf{IN}}}{2}\right)^2 / \mathsf{R}$$

The fast recovery diode must have a reverse voltage rating greater than $V_{\text{CLAMP}}.$

FIGURE 21. Snubber Circuit

FLYBACK REGULATOR CIRCUIT EXAMPLE

The circuit of *Figure 22* produces \pm 15V (at 225 mA each) from a single 5V input. The output regulation of this circuit is shown in *Figure 23* and *Figure 25*, while the load transient response is shown in *Figure 24* and *Figure 26*. Switching waveforms seen in this circuit are shown in *Figure 27*.

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.