

# SN54ABT16952, SN74ABT16952 16-BIT REGISTERED TRANSCEIVERS WITH 3-STATE OUTPUTS

SCBS082C – FEBRUARY 1991 – REVISED JANUARY 1997

- Members of the Texas Instruments **Widebus™** Family
- State-of-the-Art **EPIC-II B™** BiCMOS Design Significantly Reduces Power Dissipation
- Latch-Up Performance Exceeds 500 mA Per JEDEC Standard JESD-17
- Typical  $V_{OLP}$  (Output Ground Bounce) < 1 V at  $V_{CC} = 5$  V,  $T_A = 25^\circ\text{C}$
- Distributed  $V_{CC}$  and GND Pin Configuration Minimizes High-Speed Switching Noise
- Flow-Through Architecture Optimizes PCB Layout
- High-Drive Outputs (–32-mA  $I_{OH}$ , 64-mA  $I_{OL}$ )
- Package Options Include Plastic 300-mil Shrink Small-Outline (DL) and Thin Shrink Small-Outline (DGG) Packages and 380-mil Fine-Pitch Ceramic Flat (WD) Package Using 25-mil Center-to-Center Spacings

## description

The 'ABT16952 are 16-bit registered transceivers that contain two sets of D-type flip-flops for temporary storage of data flowing in either direction. The 'ABT16952 can be used as two 8-bit transceivers or one 16-bit transceiver. Data on the A or B bus is stored in the registers on the low-to-high transition of the clock (CLKAB or CLKBA) input provided that the clock-enable (CLKENAB or CLKENBA) input is low. Taking the output-enable ( $\overline{OEAB}$  or  $\overline{OEBA}$ ) input low accesses the data on either port.

To ensure the high-impedance state during power up or power down,  $\overline{OE}$  should be tied to  $V_{CC}$  through a pullup resistor; the minimum value of the resistor is determined by the current-sinking capability of the driver.

The SN54ABT16952 is characterized for operation over the full military temperature range of  $-55^\circ\text{C}$  to  $125^\circ\text{C}$ . The SN74ABT16952 is characterized for operation from  $-40^\circ\text{C}$  to  $85^\circ\text{C}$ .

## SN54ABT16952 . . . WD PACKAGE SN74ABT16952 . . . DGG OR DL PACKAGE (TOP VIEW)

|                       |    |    |                       |
|-----------------------|----|----|-----------------------|
| $\overline{1OEAB}$    | 1  | 56 | $\overline{1OEBA}$    |
| $\overline{1CLKAB}$   | 2  | 55 | $\overline{1CLKBA}$   |
| $\overline{1CLKENAB}$ | 3  | 54 | $\overline{1CLKENBA}$ |
| GND                   | 4  | 53 | GND                   |
| 1A1                   | 5  | 52 | 1B1                   |
| 1A2                   | 6  | 51 | 1B2                   |
| $V_{CC}$              | 7  | 50 | $V_{CC}$              |
| 1A3                   | 8  | 49 | 1B3                   |
| 1A4                   | 9  | 48 | 1B4                   |
| 1A5                   | 10 | 47 | 1B5                   |
| GND                   | 11 | 46 | GND                   |
| 1A6                   | 12 | 45 | 1B6                   |
| 1A7                   | 13 | 44 | 1B7                   |
| 1A8                   | 14 | 43 | 1B8                   |
| 2A1                   | 15 | 42 | 2B1                   |
| 2A2                   | 16 | 41 | 2B2                   |
| 2A3                   | 17 | 40 | 2B3                   |
| GND                   | 18 | 39 | GND                   |
| 2A4                   | 19 | 38 | 2B4                   |
| 2A5                   | 20 | 37 | 2B5                   |
| 2A6                   | 21 | 36 | 2B6                   |
| $V_{CC}$              | 22 | 35 | $V_{CC}$              |
| 2A7                   | 23 | 34 | 2B7                   |
| 2A8                   | 24 | 33 | 2B8                   |
| GND                   | 25 | 32 | GND                   |
| $\overline{2CLKENAB}$ | 26 | 31 | $\overline{2CLKENBA}$ |
| $\overline{2CLKAB}$   | 27 | 30 | $\overline{2CLKBA}$   |
| $\overline{2OEAB}$    | 28 | 29 | $\overline{2OEBA}$    |



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

Widebus and EPIC-II B are trademarks of Texas Instruments Incorporated.

UNLESS OTHERWISE NOTED this document contains PRODUCTION DATA information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 1997, Texas Instruments Incorporated

# SN54ABT16952, SN74ABT16952

## 16-BIT REGISTERED TRANSCEIVERS

### WITH 3-STATE OUTPUTS

SCBS082C – FEBRUARY 1991 – REVISED JANUARY 1997

FUNCTION TABLE†

| INPUTS                      |                |                          |   | OUTPUT<br>B      |
|-----------------------------|----------------|--------------------------|---|------------------|
| $\overline{\text{CLKENAB}}$ | $\text{CLKAB}$ | $\overline{\text{OEAB}}$ | A |                  |
| H                           | X              | L                        | X | $B_0^{\ddagger}$ |
| X                           | L              | L                        | X | $B_0^{\ddagger}$ |
| L                           | $\uparrow$     | L                        | L | L                |
| L                           | $\uparrow$     | L                        | H | H                |
| X                           | X              | H                        | X | Z                |

† A-to-B data flow is shown; B-to-A data flow is similar, but uses  $\overline{\text{CLKENBA}}$ ,  $\text{CLKBA}$ , and  $\overline{\text{OEBA}}$ .

‡ Level of B before the indicated steady-state input conditions were established




POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

SN54ABT16952, SN74ABT16952  
16-BIT REGISTERED TRANSCEIVERS  
WITH 3-STATE OUTPUTS


SCBS082C – FEBRUARY 1991 – REVISED JANUARY 1997

logic symbol†



† This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

## SCBS082C – FEBRUARY 1991 – REVISED JANUARY 1997

[illegible]

# SN54ABT16952, SN74ABT16952 16-BIT REGISTERED TRANSCEIVERS WITH 3-STATE OUTPUTS

SCBS082C – FEBRUARY 1991 – REVISED JANUARY 1997

## absolute maximum ratings over operating free-air temperature range (unless otherwise noted)<sup>†</sup>

|   |                 |
|---|-----------------|
| Supply voltage range, $V_{CC}$  | –0.5 V to 7 V   |
| Input voltage range, $V_I$ (except I/O ports) (see Note 1)                | –0.5 V to 7 V   |
| Voltage range applied to any output in the high or power-off state, $V_O$ | –0.5 V to 5.5 V |
| Current into any output in the low state, $I_O$ : SN54ABT16952            | 96 mA           |
| SN74ABT16952  | 128 mA          |
| Input clamp current, $I_{IK}$ ( $V_I < 0$ )                               | –18 mA          |
| Output clamp current, $I_{OK}$ ( $V_O < 0$ )                              | –50 mA          |
| Package thermal impedance, $\theta_{JA}$ (see Note 2): DGG package        | 81°C/W          |
| DL package  | 74°C/W          |
| Storage temperature range, $T_{stg}$                                      | –65°C to 150°C  |

<sup>†</sup> Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

- NOTES: 1. The input and output negative-voltage ratings may be exceeded if the input and output clamp-current ratings are observed.  
2. The package thermal impedance is calculated in accordance with EIA/JEDEC Std JESD51.

## recommended operating conditions (see Note 3)

|                     |                                    | SN54ABT16952    |          | SN74ABT16952 |          | UNIT |
|---------------------|------------------------------------|-----------------|----------|--------------|----------|------|
|                     |                                    | MIN             | MAX      | MIN          | MAX      |      |
| $V_{CC}$            | Supply voltage                     | 4.5             | 5.5      | 4.5          | 5.5      | V    |
| $V_{IH}$            | High-level input voltage           | 2               |          | 2            |          | V    |
| $V_{IL}$            | Low-level input voltage            |                 | 0.8      |              | 0.8      | V    |
| $V_I$               | Input voltage                      | 0               | $V_{CC}$ | 0            | $V_{CC}$ | V    |
| $I_{OH}$            | High-level output current          |                 | –24      |              | –32      | mA   |
| $I_{OL}$            | Low-level output current           |                 | 48       |              | 64       | mA   |
| $\Delta t/\Delta v$ | Input transition rise or fall rate | Outputs enabled |          |              |          | ns/V |
| $T_A$               | Operating free-air temperature     | –55             | 125      | –40          | 85       | °C   |

NOTE 3: Unused pins (input or I/O) must be held high or low to prevent them from floating.

# SN54ABT16952, SN74ABT16952

## 16-BIT REGISTERED TRANSCEIVERS

### WITH 3-STATE OUTPUTS

SCBS082C – FEBRUARY 1991 – REVISED JANUARY 1997

**electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)**

| PARAMETER          |                | TEST CONDITIONS  | T <sub>A</sub> = 25°C |      |       | SN54ABT16952 |      | SN74ABT16952 |      | UNIT |
|--------------------|----------------|--|-----------------------|------|-------|--------------|------|--------------|------|------|
|                    |                |  | MIN                   | TYP† | MAX   | MIN          | MAX  | MIN          | MAX  |      |
| V <sub>IK</sub>    |                | V <sub>CC</sub> = 4.5 V, I <sub>I</sub> = -18 mA                                     |                       |      | -1.2  |              | -1.2 |              | -1.2 | V    |
| V <sub>OH</sub>    |                | V <sub>CC</sub> = 4.5 V, I <sub>OH</sub> = -3 mA                                     | 2.5                   |      |       | 2.5          |      | 2.5          |      | V    |
|                    |                | V <sub>CC</sub> = 5 V, I <sub>OH</sub> = -3 mA                                       | 3                     |      |       | 3            |      | 3            |      |      |
|                    |                | V <sub>CC</sub> = 4.5 V  | 2                     |      |       | 2            |      |              |      |      |
|                    |                |  |                       |      |       |              |      |              | 2    |      |
| V <sub>OL</sub>    |                | V <sub>CC</sub> = 4.5 V  |                       |      | 0.55  | 0.55         |      |              |      | V    |
|                    |                |  |                       |      | 0.55* |              |      |              | 0.55 |      |
| V <sub>hys</sub>   |                |  |                       | 100  |       |              |      |              |      | mV   |
| I <sub>I</sub>     | Control inputs | V <sub>CC</sub> = 5.5 V, V <sub>I</sub> = V <sub>CC</sub> or GND                     |                       |      |       | ±1           | ±1   | ±1           |      | μA   |
|                    | A or B ports   |  |                       |      |       |              |      |              |      |      |
| I <sub>OZH</sub> ‡ |                | V <sub>CC</sub> = 5.5 V, V <sub>O</sub> = 2.7 V                                      |                       |      | 50    |              | 50   |              | 50   | μA   |
| I <sub>OZL</sub> ‡ |                | V <sub>CC</sub> = 5.5 V, V <sub>O</sub> = 0.5 V                                      |                       |      | -50   |              | -50  |              | -50  | μA   |
| I <sub>off</sub>   |                | V <sub>CC</sub> = 0, V <sub>I</sub> or V <sub>O</sub> ≤ 4.5 V                        |                       |      | ±100  |              |      |              | ±100 | μA   |
| I <sub>CEX</sub>   |                | V <sub>CC</sub> = 5.5 V, V <sub>O</sub> = 5.5 V                                      |                       |      | 50    |              | 50   |              | 50   | μA   |
| I <sub>O</sub> §   |                | V <sub>CC</sub> = 5.5 V, V <sub>O</sub> = 2.5 V                                      | -50                   | -100 | -200  | -50          | -200 | -50          | -200 | mA   |
| I <sub>CC</sub>    | A or B ports   | V <sub>CC</sub> = 5.5 V, I <sub>O</sub> = 0, V <sub>I</sub> = V <sub>CC</sub> or GND |                       |      |       | 2            | 2    | 2            |      | mA   |
|                    |                |  |                       |      |       |              |      |              |      |      |
|                    |                |  |                       |      |       |              |      |              |      |      |
| ΔI <sub>CC</sub> ¶ |                | V <sub>CC</sub> = 5.5 V, One input at 3.4 V, Other inputs at V <sub>CC</sub> or GND  |                       |      | 0.5   |              | 0.5  |              | 0.5  | mA   |
| C <sub>i</sub>     | Control inputs | V <sub>I</sub> = 2.5 V or 0.5 V  |                       |      | 3     |              |      |              |      | pF   |
| C <sub>io</sub>    | A or B ports   | V <sub>O</sub> = 2.5 V or 0.5 V  |                       |      | 8.5   |              |      |              |      | pF   |

\* On products compliant to MIL-PRF-38535, this parameter does not apply.

† All typical values are at V<sub>CC</sub> = 5 V.

‡ The parameters I<sub>OZH</sub> and I<sub>OZL</sub> include the input leakage current.

§ Not more than one output should be tested at a time, and the duration of the test should not exceed one second.

¶ This is the increase in supply current for each input that is at the specified TTL voltage level rather than V<sub>CC</sub> or GND.

# SN54ABT16952, SN74ABT16952 16-BIT REGISTERED TRANSCEIVERS WITH 3-STATE OUTPUTS

SCBS082C – FEBRUARY 1991 – REVISED JANUARY 1997

timing requirements over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see Figure 1)

|                    |  |  | $V_{CC} = 5\text{ V}$ ,<br>$T_A = 25^\circ\text{C}$ |     | SN54ABT16952 |     | SN74ABT16952 |     | UNIT |
|--------------------|--|--|---|-----|--------------|-----|--------------|-----|------|
|                    |  |  | MIN   | MAX | MIN          | MAX | MIN          | MAX |      |
| $f_{\text{clock}}$ | Clock frequency  |  | 0   | 150 | 0            | 150 | 0            | 150 | MHz  |
| $t_w^\dagger$      | Pulse duration, CLKAB or CLKBA high or low                 |  | 3.3   |     | 3.3          |     | 3.3          |     | ns   |
| $t_{\text{su}}$    | Setup time,<br>before CLKAB $\uparrow$ or CLKBA $\uparrow$ | A or B   | 3.5   |     | 3.5          |     | 3.5          |     | ns   |
|                    |  | $\overline{\text{CLKENAB}}$ or $\overline{\text{CLKENBA}}$ | 3   |     | 3            |     | 3            |     |      |
| $t_h$              | Hold time,<br>after CLKAB $\uparrow$ or CLKBA $\uparrow$   | A or B   | 1   |     | 1            |     | 1            |     | ns   |
|                    |  | $\overline{\text{CLKENAB}}$ or $\overline{\text{CLKENBA}}$ | 1   |     | 1            |     | 1            |     |      |

$^\dagger$  This parameter is warranted, but not production tested.

switching characteristics over recommended ranges of supply voltage and operating free-air temperature,  $C_L = 50\text{ pF}$  (unless otherwise noted) (see Figure 1)

| PARAMETER        | FROM<br>(INPUT)        | TO<br>(OUTPUT) | $V_{CC} = 5\text{ V}$ ,<br>$T_A = 25^\circ\text{C}$ |     |     | SN54ABT16952 |     | SN74ABT16952 |     | UNIT |
|------------------|------------------------|----------------|---|-----|-----|--------------|-----|--------------|-----|------|
|                  |                        |                | MIN   | TYP | MAX | MIN          | MAX | MIN          | MAX |      |
| $f_{\text{max}}$ |                        |                | 150   |     |     | 150          |     | 150          |     | MHz  |
| $t_{\text{PLH}}$ | CLK                    | A or B         | 1   | 2.6 | 3.9 | 1            | 4.4 | 1            | 4.3 | ns   |
| $t_{\text{PHL}}$ |                        |                | 1   | 2.6 | 4.2 | 1            | 4.6 | 1            | 4.5 |      |
| $t_{\text{PZH}}$ | $\overline{\text{OE}}$ | A or B         | 1   | 2.5 | 3.8 | 1            | 4.7 | 1            | 4.6 | ns   |
| $t_{\text{PZL}}$ |                        |                | 1   | 2.8 | 5.1 | 1            | 6.1 | 1            | 6   |      |
| $t_{\text{PHZ}}$ | $\overline{\text{OE}}$ | A or B         | 1.7   | 3.4 | 4.7 | 1.7          | 6.1 | 1.7          | 5.5 | ns   |
| $t_{\text{PLZ}}$ |                        |                | 1.3   | 3   | 3.9 | 1.3          | 4.8 | 1.3          | 4.2 |      |

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.




POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

# SN54ABT16952, SN74ABT16952 16-BIT REGISTERED TRANSCIEVERS WITH 3-STATE OUTPUTS


SCBS082C – FEBRUARY 1991 – REVISED JANUARY 1997

## PARAMETER MEASUREMENT INFORMATION




LOAD CIRCUIT


| TEST              | S1   |
|-------------------|------|
| $t_{PLH}/t_{PHL}$ | Open |
| $t_{PLZ}/t_{PZL}$ | 7 V  |
| $t_{PHZ}/t_{PZH}$ | Open |




VOLTAGE WAVEFORMS  
PULSE DURATION



VOLTAGE WAVEFORMS  
SETUP AND HOLD TIMES



VOLTAGE WAVEFORMS  
PROPAGATION DELAY TIMES  
INVERTING AND NONINVERTING OUTPUTS



VOLTAGE WAVEFORMS  
ENABLE AND DISABLE TIMES  
LOW- AND HIGH-LEVEL ENABLING

- NOTES: A.  $C_L$  includes probe and jig capacitance.  
B. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.  
C. All input pulses are supplied by generators having the following characteristics:  $PRR \leq 10 \text{ MHz}$ ,  $Z_O = 50 \Omega$ ,  $t_r \leq 2.5 \text{ ns}$ ,  $t_f \leq 2.5 \text{ ns}$ .  
D. The outputs are measured one at a time with one transition per measurement.

Figure 1. Load Circuit and Voltage Waveforms



## PACKAGING INFORMATION

| Orderable Device  | Status <sup>(1)</sup> | Package Type | Package Drawing | Pins | Package Qty | Eco Plan <sup>(2)</sup> | Lead/Ball Finish | MSL Peak Temp <sup>(3)</sup> |
|-------------------|-----------------------|--------------|-----------------|------|-------------|-------------------------|------------------|------------------------------|
| 74ABT16952DGGRE4  | ACTIVE                | TSSOP        | DGG             | 56   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74ABT16952DGGR  | ACTIVE                | TSSOP        | DGG             | 56   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74ABT16952DL    | ACTIVE                | SSOP         | DL              | 56   | 20          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74ABT16952DLR   | ACTIVE                | SSOP         | DL              | 56   | 1000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74ABT16952DLRG4 | ACTIVE                | SSOP         | DL              | 56   | 1000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |

<sup>(1)</sup> The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

<sup>(2)</sup> Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS) or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

**TBD:** The Pb-Free/Green conversion plan has not been defined.

**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

**Green (RoHS & no Sb/Br):** TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

<sup>(3)</sup> MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

| <b>Products</b>  |  | <b>Applications</b> |  |
|------------------|--|---------------------|--|
| Amplifiers       | <a href="http://amplifier.ti.com">amplifier.ti.com</a>             | Audio               | <a href="http://www.ti.com/audio">www.ti.com/audio</a>                   |
| Data Converters  | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>     | Automotive          | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>         |
| DSP              | <a href="http://dsp.ti.com">dsp.ti.com</a>                         | Broadband           | <a href="http://www.ti.com/broadband">www.ti.com/broadband</a>           |
| Interface        | <a href="http://interface.ti.com">interface.ti.com</a>             | Digital Control     | <a href="http://www.ti.com/digitalcontrol">www.ti.com/digitalcontrol</a> |
| Logic            | <a href="http://logic.ti.com">logic.ti.com</a>                     | Military            | <a href="http://www.ti.com/military">www.ti.com/military</a>             |
| Power Mgmt       | <a href="http://power.ti.com">power.ti.com</a>                     | Optical Networking  | <a href="http://www.ti.com/opticalnetwork">www.ti.com/opticalnetwork</a> |
| Microcontrollers | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a> | Security            | <a href="http://www.ti.com/security">www.ti.com/security</a>             |
|                  |  | Telephony           | <a href="http://www.ti.com/telephony">www.ti.com/telephony</a>           |
|                  |  | Video & Imaging     | <a href="http://www.ti.com/video">www.ti.com/video</a>                   |
|                  |  | Wireless            | <a href="http://www.ti.com/wireless">www.ti.com/wireless</a>             |

Mailing Address: Texas Instruments  
Post Office Box 655303 Dallas, Texas 75265

Copyright © 2005, Texas Instruments Incorporated