

TOSHIBA Photocoupler GaAs Ired & Photo-Thyristor

TLP541G, TLP542G

Programmable Controllers

AC-Output Module


Solid State Relay

The TOSHIBA TLP541G consists of a photo-thyristor optically coupled to a gallium arsenide infrared emitting diode in a six lead plastic DIP package.


The TOSHIBA TLP542G consists of a photo-thyristor optically coupled to a gallium arsenide infrared emitting diode in a seven lead plastic DIP package.

- Peak off-state voltage: 400 V (min.)
- Trigger LED current: 7 mA (max.)
- On-state current: 150 mA (max.)
- Isolation voltage: 2500 V_{rms} (min.)
- UL recognized: UL1577, file no. E67349

Pin Configuration (top view)




1 : ANODE
2 : CATHODE
3 : N.C.
4 : CATHODE
5 : ANODE
6 : GATE




1 : N.C.
2 : ANODE
3 : CATHODE
4 : N.C.
5 : GATE
6 : CATHODE
7 : ANODE

Unit in mm



Weight: 0.4 g



Weight: 0.53 g

Maximum Ratings (Ta = 25°C)

| Characteristic | | Symbol | Rating | Unit |
|---|--|-------------------------------|---------|-----------|
| LED | Forward current | I_F | 70 | mA |
| | Forward current derating (Ta ≥ 25°C) | $\Delta I_F / ^\circ\text{C}$ | -0.7 | mA / °C |
| | Peak forward current (100 μs pulse, 100 pps) | I_{FP} | 1 | A |
| | Reverse voltage | V_R | 5 | V |
| | Junction temperature | T_j | 125 | °C |
| Detector | Peak forward voltage (RGK = 27kΩ) | V_{DRM} | 400 | V |
| | Peak reverse voltage (RGK = 27kΩ) | V_{RRM} | 400 | V |
| | On-state current | I_T (RMS) | 150 | mA |
| | On-state current derating (Ta ≥ 25°C) | $\Delta I_T / ^\circ\text{C}$ | -2.0 | mA / °C |
| | Peak one cycle surge current | I_{TSM} | 2 | A |
| | Peak reverse gate voltage | V_{GM} | -5 | V |
| | Junction temperature | T_j | 100 | °C |
| Storage temperature range | | T_{stg} | -55~125 | °C |
| Operating temperature range | | T_{opr} | -30~100 | °C |
| Lead soldering temperature (10 s) | | T_{sol} | 260 | °C |
| Isolation voltage (AC, 1 min., R.H. ≤ 60%) (Note) | | BV_S | 2500 | V_{rms} |

(Note) Device considered a two terminal device: LED side pins shorted together and detector side pins shorted together.

Recommended Operating Conditions







| Characteristic | Symbol | Min. | Typ. | Max. | Unit |
|----------------------------|-----------|------|------|------|----------|
| Supply voltage | V_{AC} | — | — | 120 | V_{ac} |
| Forward current | I_F | 10 | 16 | 25 | mA |
| Operating temperature | T_{opr} | -30 | — | 85 | °C |
| Gate to cathode resistance | R_{GK} | — | 27 | 33 | kΩ |
| Gate to cathode capacity | C_{GK} | — | 0.01 | 0.1 | μF |








Individual Electrical Characteristics (Ta = 25°C)

| Characteristic | | Symbol | Test Condition | | Min. | Typ. | Max. | Unit |
|----------------|-------------------|-----------|---|------------|------|------|------|------------------|
| LED | Forward voltage | V_F | $I_F = 10 \text{ mA}$ | | 1.0 | 1.15 | 1.3 | V |
| | Reverse current | I_R | $V_R = 5 \text{ V}$ | | — | — | 10 | μA |
| | Capacitance | C_T | $V = 0, f = 1 \text{ MHz}$ | | — | 30 | — | pF |
| Detector | Off-state current | I_{DRM} | $V_{AK} = 400 \text{ V}$ $R_{GK} = 27 \text{ k}\Omega$ | Ta = 25°C | — | 10 | 5000 | nA |
| | | | | Ta = 100°C | — | 1 | 100 | μA |
| | Reverse current | I_{RRM} | $V_{KA} = 400 \text{ V}$ $R_{GK} = 27 \text{ k}\Omega$ | Ta = 25°C | — | 10 | 5000 | nA |
| | | | | Ta = 100°C | — | 1 | 100 | μA |
| | On-state voltage | V_{TM} | $I_{TM} = 100 \text{ mA}$ | | — | 0.9 | 1.3 | V |
| | Holding current | I_H | $R_{GK} = 27 \text{ k}\Omega$ | | — | 0.2 | 1 | mA |
| | Off-state dv/dt | dv/dt | $V_{AK} = 280 \text{ V}, R_{GK} = 27 \text{ k}\Omega$ | | 5 | 10 | — | V/ μs |
| | Capacitance | C_j | V = 0, f = 1 MHz | | — | 20 | — | pF |
| | | | Anode to gate Gate to cathode | | — | 350 | — | |

Coupled Characteristics (Ta = 25°C)

| Characteristic | Symbol | Test Condition | Min. | Typ. | Max. | Unit |
|-------------------------------|----------|---|------|-----------|------|---------------|
| Trigger LED current | I_{FT} | $V_{AK} = 6 \text{ V}, R_{GK} = 27 \text{ k}\Omega$ | 1 | 4 | 7 | mA |
| Turn-on time | t_{on} | $I_F = 50 \text{ mA}, R_{GK} = 27 \text{ k}\Omega$ | — | 10 | — | μs |
| Capacitance (input to output) | C_S | $V_S = 0, f = 1 \text{ MHz}$ | — | 0.8 | — | pF |
| Isolation resistance | R_S | $V_S = 500 \text{ V}, \text{R.H.} \leq 60\%$ | — | 10^{11} | — | Ω |
| Isolation voltage | BV_S | AC, 1 minute | 2500 | — | — | V_{rms} |





RESTRICTIONS ON PRODUCT USE

000707EAA

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.