

ViewSonic VG700 Monitor datasheet

<http://www.manuallib.com/viewsonic/vg700-monitor-datasheet.html>

ViewSonic's 17" VG700 LCD display combines multimedia performance and value in a stylish package. Special features include a high 450:1 contrast ratio and 260-nit brightness for vibrant, rich colour and sharp text. OSD and power lock functions with Ø-Touch™ AutoTune™ optimise monitor settings for a superior panel image. Two 3-watt bezel-integrated speakers are ideal for multimedia applications like videoconferencing and the slim, two-tone metallic-on-black design works well with black-case computers. ViewSonic's VG700 LCD - for brilliant performance at home or the office.

ManualLib.com collects and classifies the global product instruction manuals to help users access anytime and anywhere, helping users make better use of products.

<http://www.manuallib.com>

ViewSonic®

VG700 LCD Monitor



The 17" VG700 multimedia LCD is a real performer.

ViewSonic's 17" VG700 LCD display combines multimedia performance and value in a stylish package. Special features include a high 450:1 contrast ratio and 260-nit brightness for vibrant, rich colour and sharp text. OSD and power lock functions with Ø-Touch™ AutoTune™ optimise monitor settings for a superior panel image. Two 3-watt bezel-integrated speakers are ideal for multimedia applications like videoconferencing and the slim, two-tone metallic-on-black design works well with black-case computers. ViewSonic's VG700 LCD - for brilliant performance at home or the office.

- **Full 17.0" viewable screen**
- **1280x1024 optimum resolution (1.3 megapixels)**
Displays a maximum resolution of 1280x1024; scalable resolution from VGA up to 1280x1024.
- **260 nits of high brightness**
- **450:1 high contrast ratio**
- **OnView® controls including ViewMatch® feature**
Screen adjustments are made via the OnView menu using simple on-screen controls. ViewMatch allows easy adjustment to colour temperature and intensity for optimal screen-to-print colour matching.
- **AutoTune™ function**
Automatically monitors video input and optimises display settings without requiring user adjustments.
- **Bezel-integrated speakers**
The two 3-watt built-in audio speakers save desk and workspace while offering superior sound quality.
- **OSD key lock and power lock**
The key lock function locks the menu settings to protect from accidental or unwanted changes. The power lock prevents the monitor from being inadvertently switched off.
- **Stylish and slim 2.3" profile (panel only)**



ViewSonic®
See the difference.™

www.ViewSonicEurope.com

ViewSonic®

VG700 LCD Monitor



17" Multimedia TFT LCD


LCD PANEL	Type	TFT active matrix SXGA LCD (16.7 million colours)
	Display Area	17" diagonal (338mm H x 270mm V)
	Pixel Pitch	0.264mm
	Contrast Ratio	450:1 (max.)
	Viewing Angle	140° horizontal, 135° vertical (typical at 10:1)
	Light Source	Long life, 50,000 hrs. (typical)
	Response Time	16ms (typical)
VIDEO INPUT	Brightness	260 cd/m ² (typ.)
	Panel Surface	Anti-glare
	Analogue Frequency Sync	RGB Analogue (75 ohms, 0.7 Vp-p) F _H :30-82kHz, f _V :50-85Hz H/V separated (TTL)
COMPATIBILITY	PC	IBM compatible from VGA up to 1280x1024 NI
	Mac^{®1}	Power Mac™ G3/G4 up to 1280x1024
CONNECTOR	Analogue	15-pin mini D-sub (detachable)
	Audio	3.5mm stereo jack line-in
	Power	DC In, DC to Head (12V)
AUDIO	Speakers	2 x 3 watts (frequency 200Hz - 20kHz)
	Amplifier	3 watts @1kHz
POWER	Voltage Consumption	AC 100-240V, 50/60Hz (auto switch), external Power Supply 35W (max)
CONTROLS	Basics	Power On/Off, Menu, up/down, Select, Mute, Audio +/-
	OSD	Contrast, Brightness, Auto Image Adjust, Manual Image Adjust (H Size, H/V Position, Fine Tune, Sharpness), Colour Adjust (9300K, 6500K, user), Audio (Volume, Mute), Display Information (Resolution, Frequency, Model-/Serialnumber), OSD Setup Menu (Language, Resolution notice, H/V Position, Time out), Memory Recall, OSD Lock, Power Lock
OPERATING CONDITIONS	Temperature Humidity	0°C to 40°C (32°F to 104°F) 10% to 90% (non-condensation)
DIMENSIONS	Physical	410mm (W) x 421mm (H) x 192mm (D) (16,1" x 16,6" x 7,5")
WEIGHT	Net	5.2kgs (11.4lbs.)
PLUG & PLAY		DDC1, DDC2B
REGULATIONS		TCO'99, TÜV/GS, TÜV/Ergo, ISO 13406-2 (class 2), ISO 9241-3, ISO 9241-7, ISO 9241-8, Energy 2000, CE, CB, FCC-B, UL, NEMKO, SEMKO, DEMKO, FIMKO, VCCI, BSMI, PSB, PCBC, C-Tick, Gost-R, SASO, PC'2001
POWER MANAGEMENT		ENERGY STAR®, VESA® DPMS, TCO'99, Energy 2000
WARRANTY		Three-year limited warranty ³ .

• ViewSonic Wizard

This software provides user-friendly installation. The included CD-ROM automates the set-up process to deliver optimised screen performance.

• TCO '99 and Energy 2000 certified

This monitor complies with the world's strictest standards for low emissions, safety, ergonomics, recycling and power management while saving costs through automatic power saving modes.



• PC and Mac[®] compatible¹

• Kensington[®] lock ready

Protect your assets with this attachment for an anti-theft cable.

• VESA[®] mount compliant²

• Three-year limited warranty³

• Cable Management

The smart idea against unsightly wayward cables and for added security: cables are neatly concealed right down to the monitor's base.



ViewSonic Corporation's QMS/EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.



ViewSonic®
See the difference.™

www.ViewSonicEurope.com

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux
ViewSonic Denmark
ViewSonic Finland
ViewSonic Italy
ViewSonic MEA
ViewSonic Norway
ViewSonic Spain
ViewSonic Sweden

Tel: +32 056/85 26 27
Tel: +45 70 22 11 71
Tel: +358 (9) 54 06 40 70
Tel: +39 0289 079 340
Tel: +971 (0) 4 88 11 871
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹May require optional Mac adapter. ²Wall mount accessories are optional. ³For further information see ViewSonic Website.
Copyright © 2004, ViewSonic Corporation. All rights reserved. Corporate names and trademarks stated herein are the property of their respective companies. Specifications subject to change without notice. The EPA only promotes energy efficiency and does not endorse any particular company or product. VS VG700 03/04-UK