

# SAMPO LME-65D Monitor datasheet

<http://www.manuallib.com/sampo/lme-65d-monitor-datasheet.html>

Aspect Ratio 16:9

Resolution 1920(H)x1080P(V)

Pixel Pitch 0.744mm(H)x0.744mm(V)

Contrast Ratio 5000:1

Brightness 450 cd/m<sup>2</sup>

Display Colors 1.06 Billion Colors

ManualLib.com collects and classifies the global product instruction manuals to help users access anytime and anywhere, helping users make better use of products.

<http://www.manuallib.com>

# LME-65D Specification



65"

## Digital Signage Monitor

120Hz/240Hz

### Features

- 65" Full HD LCD Display ■
- 3D Comb Filter Supported ■
- Support RS-232 Control Function ■
- High Contrast Ratio 5000:1 ■
- RoHS Compliant ■

### Display

- Aspect Ratio 16:9
- Resolution 1920 (H) x 1080P (V)
- Pixel Pitch 0.744 mm (H) x 0.744 mm (V)
- Contrast Ratio 5000:1
- Brightness 450 cd/m<sup>2</sup>
- Display Colors 1.06 Billion Colors

### Signal

- Horizontal Frequency 15~64 kHz
- Vertical Frequency 50~70 Hz
- Video System NTSC/PAL
- VESA Resolution Support via RGB Up to 1920 x 1080P

### Video Input

- Composite Input x 1
- S-Video x 1
- Component Video Input x 1
- HDMI Input x 1
- RGB Input (D-Sub) x 1

### Audio Input

- Audio Input x 5

### Audio Output

- Audio Output x 1

### Control Port

- RS-232 x 1

### Optional Accessory

- Stand / Speaker / Wall Mount



RoHS



Product design and specification are subject to change without notice.